


MEMS 192X192 OPTICAL SWITCHING SYSTEM

OSS Model, Single Mode Fiber, Quantum Grade



DiCon's **Optical Switching System (OSS)** is an all-optical non-blocking cross-connect switch. This rack-mount device is designed with DiCon's proprietary 3D MEMS mirror technology and delivers industry-leading optical performance. The unit works without any position sensor or feedback loop, and the optical signals can pass through the equipment without any observable dithering artifacts. The **OSS** can switch repeatedly with great accuracy and maintain long-term connectivity with superior stability even when there is no optical signal in the fiber.

The chassis is compact, taking minimal rack space. It is also lightweight and can be picked up easily for installation. The **OSS** comes with multiple control interfaces so authorized administrators can automate network management and set user permissions in a Software Defined Network (SDN). This product can be ordered in standard simplex or duplex configurations, and customized port arrangements are available upon request. Optical power monitors and attenuators can be added to each path as options.

Key Features

- Market Leading Performance with Recognized Reliability
- Low Loss with High Stability & No Dithering Artifacts
- Compact, Lightweight, Easy to Transport
- Switches Fast & Consumes Low Power
- Operates Bi-Directionally & Works with Dark Fibers
- Supports Software Defined Networks

Applications

- Optical Network Management
- Quantum Communications
- Data Center Interconnect
- AI (Artificial Intelligence) Networks
- LLM (Large Language Models) Machine Training
- Cyber Security & Monitoring
- Network Test Automation

ORDERING INFORMATION

OSS - Q - - - 9 - - - - -

Grade	Quantum
Configuration	S192x192 Simplex 192x192 SMxN Simplex (M, N≤192) D192 Duplex 192 Ports D# Duplex (#≤192)
Function	S Matrix Switch Only SA VOA Only MS M Side Power Monitor MSA M Side Power Monitor & VOA SN N Side Power Monitor SAN N Side Power Monitor & VOA MSN Both Sides Power Monitor MSAN Both Sides Power Monitor & VOA D Matrix Switch Only DA VOA Only DP Power Monitor (B Ports / Outputs) DAP Power Monitor & VOA (B Ports / Outputs)
Fiber Type	9 9/125 μm SMF <i>*Other fiber options available upon request</i>
Test Wavelength	O 1310 nm C 1550 nm L 1590 nm <i>*Use "/" to add multiple wavelengths. E.g., O/C or O/C/L</i>
Chassis Height	3U 3U 4U 4U 6U 6U <i>*Contact Sales for assistance</i>
Power	A1 AC 100-240V Single D1 DC -48V Single A2 AC 100-240V Redundant D2 DC -48V Redundant
Connector Type	LC LC/APC LC/APC LC/APC RLC LC/APC on Removable Panel RLC/APC LC/APC on Removable Panel HLC High Density LC UPC HLC/APC High Density LC APC M8 MTP/MPO-8 APC M12 MTP/MPO-12 APC <i>*Other connector types available upon request</i>
Connector Location	F Front R Rear


MEMS 192X192 OPTICAL SWITCHING SYSTEM

OSS Model, Single Mode Fiber, Quantum Grade

OPTICAL SPECIFICATIONS¹

Operating Wavelength	1260 to 1675 nm
Insertion Loss ²	< 1.9 dB
Insertion Loss (with 1 OPM) ²	< 2.2 dB
Insertion Loss (with 2 OPM) ²	< 2.5 dB
Loss Repeatability ³	+/- 0.01 dB
Connection Stability ^{4,5}	+/- 0.01 dB
Connection Stability (Short Term) ⁶	+/- 0.005 dB
PDL ⁵	< 0.1 dB
PDL with OPM ⁵	< 0.3 dB
WDL ^{5,7}	< 0.3 dB
Crosstalk	< -70 dB
Data Latency ⁵	< 15 ns
Back Reflection	< -50 dB
Optical Transition Time ^{5,8}	< 25 ms
Switch Lifetime	> 1 Billion Cycles
Input Power Range	Dark to +27 dBm
OPM Dynamic Range	-50 to +22 dBm
OPM Relative Accuracy	+/-0.2 dB @ > -30dBm +/-0.5 dB @ > -50dBm

1. Measured separately for each Test Wavelength
2. Measured with 3-jumper method or equivalent. See TIA/EIA 526-7.
3. Over 100 cycles
4. 1 Hz sampling rate for 15 min
5. Met by design, not measured
6. 10 KHz sampling rate for 10 Sec
7. Test Wavelength +/-20nm
8. Optical transition time for all ports switching concurrently, not including command processing overhead



ELECTRICAL SPECIFICATIONS

Power Consumption ⁹	< 55W Steady State < 65W at Startup
Power Supply Options	Redundant Power Supply, 100-240 VAC or -48 VDC
Network Interface Card	RJ45 Dual Redundant Gigabit Ethernet
SDN & Automation Interfaces	REST API, NETCONF, SNMPv3, TL1, Web GUI, RS232

9. Power is measured with 2 OPM

ENVIRONMENTAL SPECIFICATIONS

Operating Temperature	0 to 50°C, < 85% RH
Storage Temperature	-40 to 70°C, < 40% RH

MECHANICAL SPECIFICATIONS

19" Chassis Depth	559 mm (22")
19" Chassis Height	3U (with HD LC)

