


MEMS 96X96 OPTICAL SWITCHING SYSTEM

GP800 Model, Single Mode Fiber



DiCon's **GP800 96x96 Optical Switching System** is an all-optical non-blocking cross-connect switch. This rack-mount device is designed with DiCon's proprietary 3D MEMS mirror technology and delivers industry-leading optical performance. The unit works without any position sensor or feedback loop, and the optical signals can pass through the equipment without any observable dithering artifacts. The **GP800 System** can switch repeatedly with great accuracy and maintain long-term connectivity with superior stability even when there is no optical signal in the fiber.

The **GP800 System** comes with multiple control interfaces for users to choose from and there are many options to customize the product, including adding other optical components, to meet unique requirements.

- High-density non-blocking Matrix Switches
- Interfaces - Web GUI, SSH, RS232, REST API, Telnet
- Advanced WebGUI for port partitions
- Low insertion loss - 0.8dB typical (excluding connector loss)
- Fast switching - concurrent switching < 25 ms
- Lifetime > 1 billion switch cycles
- No position sensor nor feedback-loop used
- Works even when there is no light in the fiber
- Excellent stability with no observable dithering artifacts
- Low power consumption
- Proven MEMS platform - commercial deployment since 2001
- Low MEMS drive voltage - simple and reliable electronics
- Intelligent hardware - field serviceable electronics

ORDERING INFORMATION

GP800 - [] - SX - [] - 9 - [] - [] - N - []

Chassis Type

2U 2U
3U 3U
4U 4U
5U 5U

**Please consult DiCon*

Product Type

SX MEMS Matrix Switch

Configuration

T96x96 96x96
TMxN MxN (M, N≤96)

Fiber Type

9 9/125 μm SMF

**Other fiber options available upon request*

Test Wavelength

O 1310 nm
E 1410 nm
S 1490 nm
C 1550 nm
L 1590 nm
U 1650 nm

**Use "/" to add multiple wavelengths. E.g., O/C or O/C/L*

Connector Type

FC FC/UPC
FC/APC FC/APC
SC SC/UPC
SC/APC SC/APC
LC LC/UPC
LC/APC LC/APC
RLC LC/UPC on Removable Panel
RLC/APC LC/APC on Removable Panel

**Other connector types available upon request*

Connector Key Orientation

N None

Connector Location

F Front
R Rear

MEMS 96X96 OPTICAL SWITCHING SYSTEM

GP800 Model, Single Mode Fiber

OPTICAL SPECIFICATIONS¹

Wavelength Range	1260 to 1675 nm
Insertion Loss ²	< 1.2 dB
Loss Repeatability ³	+/- 0.03 dB
Connection Stability ^{4,5}	+/- 0.03 dB
PDL ⁵	< 0.1 dB
WDL ^{5,6}	< 0.3 dB
Crosstalk ⁵	< -60 dB
Back Reflection	< -50 dB
Optical Transition Time ^{5,7}	< 25 ms
Switch Lifetime	> 1 Billion Cycles
Input Power Range	Dark to +27 dBm

1. Measured separately for each Test Wavelength at room temperature

2. Measured with 3-jumper method or equivalent. See TIA/EIA 526-7.

3. Over 100 cycles

4. 1 Hz sampling rate for 15 min

5. Met by design, not measured

6. WDL is defined within Test Wavelength ± 20 nm

7. Optical transition time for all ports switching concurrently, not including command processing overhead

ELECTRICAL SPECIFICATIONS

Power Supply	100-240 VAC, 50/60 Hz
Connectors	RJ45 (Ethernet) DB9 (RS232) USB-C (Service)
Control Interface	Web GUI, SSH, RS232, REST API, Telnet, gNMI

ENVIRONMENTAL SPECIFICATIONS

Operating Temperature	0 to 50°C, < 85% RH
Storage Temperature	-40 to 70°C, < 40% RH

MECHANICAL SPECIFICATIONS

Chassis Width	483 mm (19")
Chassis Depth	435 mm (17")
Chassis Height	4U/5U (Front/Back, FC) 4U/5U (Front/Back, SC) 2U/3U (Front/Back, LC) 2U/3U (Front/Back, RLC)