

MEMS 1X4 OPTICAL SWITCHING SYSTEM



GP800 Model, Single Mode Fiber



DiCon's **GP800 1x4 Optical Switching System** enable the automated connection of one common fiber to any of N output fibers.

The **GP800 System** comes with multiple control interfaces for users to choose from and there are many options to customize the product, including adding other optical components, to meet unique requirements.

- Interfaces - Web GUI, SSH, RS232, REST API, Telnet
- Low insertion loss - 0.4dB typical (excluding connector loss)
- Switching time < 25 ms
- Lifetime > 1 billion switch cycles
- Low power consumption
- Proven MEMS platform - commercial deployment since 2001
- Low MEMS drive voltage - simple and reliable electronics
- Intelligent hardware - field serviceable electronics



ORDERING INFORMATION

GP800 - [] - M - [] - [] - [] - 9 - [] - [] - [] - N - []

Chassis Type	
1U	1U
2U	2U
3U	3U
4U	4U
<i>*Please consult DiCon</i>	
Product Type	
M	MEMS Switch
Number of Switches	
#	Number of Switches
Switch Type	
1x4	1x4 Simplex
1x4/DS	1x4 Duplex
Alignment Type	
T	Transparent
P	Opaque
Fiber Type	
9	9/125 μm SMF
<i>*Other fiber options available upon request</i>	
Optimized Wavelength Range	
O	1260-1360 nm
E	1360-1460 nm
S	1460-1530 nm
C	1530-1570 nm
L	1570-1625 nm
U	1625-1675 nm
<i>*Multiple wavelength ranges can be supported.</i>	
<i>Use "/" to add multiple ranges.</i>	
<i>For example: For 1260 - 1360 nm & 1530 - 1570nm use O/C,</i>	
<i>for 1260 to 1675 nm use O/E/S/C/L/U</i>	
Start Up State	
0	Channel 0 (Off state)
1	Channel 1
X	Channel X
Connector Type	
FC	FC/UPC
FC/APC	FC/APC
SC	SC/UPC
SC/APC	SC/APC
LC	LC/UPC
LC/APC	LC/APC
N	None
<i>*Other connector types available upon request</i>	
Connector Key Orientation	
N	None
Connector Location	
F	Front
R	Rear

MEMS 1X4 OPTICAL SWITCHING SYSTEM

GP800 Model, Single Mode Fiber

OPTICAL SPECIFICATIONS

Wavelength Range	1260 to 1675 nm
Insertion Loss ^{1,2}	< 0.6 dB
PDL ³	< 0.1 dB
WDL ^{4,5}	< 0.2 dB
Crosstalk	< -50 dB
Back Reflection	< -50 dB
Switching Time, All Channels	< 25 ms
Switch Lifetime	> 1 Billion Cycles
Optical Power	500 mW Max.

1. Excluding connector loss. Equivalent to Method A.3 Three Jumper (TIA/EIA-526-7). Tested at calibrated wavelengths.
2. IL add 0.3 dB for multi-band operation
3. PDL add 0.1 for multi-band operation
4. WDL add 0.1 dB for multi-band operation
5. Over the operating wavelength range of each band

ELECTRICAL SPECIFICATIONS

Power Supply	100-240 VAC, 50/60 Hz
Connectors	RJ45 (Ethernet) DB9 (RS232) USB-C (Service)
Control Interface	Web GUI, SSH, RS232, REST API, Telnet

ENVIRONMENTAL SPECIFICATIONS

Operating Temperature	0 to 50°C, < 85% RH
Storage Temperature	-40 to 70°C, < 40% RH

MECHANICAL SPECIFICATIONS

Chassis Width	483 mm (19")
Chassis Depth	435 mm (17")
Chassis Height	1U/2U (Front/Back, FC) 1U/2U (Front/Back, SC) 1U/1U (Front/Back, LC)